

# Safety Data Sheet

## 1. IDENTIFICATION

<b>Product Name:</b>	<b>Solvent DSP 80/100</b>
<b>Other Names:</b>	DSP 80/100 FLUID, SBP80/100
<b>Recommended Use:</b>	Solvent for resin, lacquers, wax, printing ink, adhesives, plastics and polishes agent. Raw material for used in the chemical industry such as paints, rubbers, plastic, cosmetics, pharmaceuticals, and dehydrate agents.
<b>Supplier:</b>	Global Chemie ASCC Limited
<b>Street Address:</b>	88/123 Moo 2 Bangpoo Industrial Estate (North), Phraek Sa Mai, Mueang Samutprakan, Samutprakan 10280
<b>Telephone:</b>	+66 2324 6888
<b>Fax:</b>	+66 2324 6898-99
<b>Emergency phone:</b>	+66 2324 6888 ext.320

## 2. HAZARDS IDENTIFICATION

### Hazardous Nature

This product is classified as hazardous under GHS criteria

### Hazardous Classification

Flammable liquid: Category 2

Skin irritation: Category 2

Specific target organ toxicant (central nervous system): Category 3

Aspiration toxicant: Category 1

Acute aquatic toxicant: Category 2

Chronic aquatic toxicant: Category 2

### Hazardous Statement

Highly Flammable liquid and vapour

### GHS Pictograms



### Hazard Statements

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P210: Keep away from heat/sparks/open flames/hot surfaces. -- No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating and lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves and eye / face protection.

#### Response Statements

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P331: Do NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/attention.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish.

P391: Collect spillage.

#### Storage Statements

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

#### Disposal Statements

P501: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied.

#### Signal Word Danger

### 3. COMPOSITION: Information on Ingredients

Hazardous Substance(s) or Complex Substance(s) required for disclosure.

Chemical Ingredient	CAS No.	UN No.	Proportion (%v/v)
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	64742-49-0	3295	100 %

Molecular Weight: 94 g/mol

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure

Chemical Ingredient	CAS No.	UN No.	Proportion (%v/v)
CYCLOHEXANE	110-82-7	1145	15 - 35%
HEPTANE AND ISOMERS	ISOMER MIXTURES	-	25 - 40%
METHYLCYCLOHEXANE	108-87-2	2296	1 - 25%
n-Hexane	110-54-3	1208	< 15%

### 4. FIRST AID MEASURES

For advice, contact Ramathibodi Poison Center (Phone: 1367) or a doctor.

**Ingestion**

Seek immediate medical attention. Do not induce vomiting.

**Eye Contact**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**Skin Contact**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing

**Inhalation**

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

**NOTE TO PHYSICIAN**

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This light hydrocarbon material, or a component, may be associated with cardiac sensitisation following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided.

**PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE**

Contains hexane; individuals with pre-existing neurological disease should avoid exposure.

**5. FIRE FIGHTING MEASURES**

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing firefighters with this Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

**Suitable extinguishing media**

**Appropriate Extinguishing Media:** Use foam, dry chemical, or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight streams of water.

**FIRE FIGHTING**

**Fire Fighting Instructions:** Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapours and to protect personnel attempting to stop a leak. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** Highly flammable. Vapour is flammable and heavier than air. Vapour may travel across the ground and reach remote ignition sources, causing a flashback fire danger. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

**Hazardous Combustion Products:** Incomplete combustion products, Oxides of carbon, Smoke, Fume.

**FLAMMABILITY PROPERTIES**

**Flash Point [Method]:** -15°C (5°F) [Approximate] [ASTM D-56]

**Flammable Limits (Approximate volume % in air):** LEL: 1.0 UEL: 7.0

**Autoignition Temperature:** >200°C (392°F)

**6. ACCIDENTAL RELEASE MEASURES****NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable

regulations.

### **PROTECTIVE MEASURES**

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H<sub>2</sub>S, or Self-Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to aromatic hydrocarbons are recommended. Note: gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

### **SPILL MANAGEMENT**

**Land Spill:** Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Large Spills: Water spray may reduce vapour but may not prevent ignition in enclosed spaces. **Water Spill:** Stop leak if you can do so without risk. Eliminate sources of ignition. Warn other shipping. If the Flash Point exceeds the Ambient Temperature by 10 deg C or more, use containment booms and remove from the surface by skimming or with suitable absorbents when conditions permit. If the Flash Point does not exceed the Ambient Air Temperature by at least 10C, use booms as a barrier to protect shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### **ENVIRONMENTAL PRECAUTIONS**

**Large Spills:** Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## **7. HANDLING AND STORAGE**

### **Precautions for safe handling**

Avoid breathing mists or vapour. Avoid contact with skin. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapour may be evolved from heated or agitated material. Use only with adequate ventilation. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

**Loading/Unloading Temperature:** [Ambient]

**Transport Temperature:** [Ambient]

**Transport Pressure:** [Ambient]

**Static Accumulator:** This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semi conductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

### **Conditions for safe storage**

Ample fire water supply should be available. A fixed sprinkler/deluge system is recommended. The type of container used to store the material may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Outside or detached storage preferred. Storage containers should be earthed and bonded. Fixed storage containers, transfer containers and associated equipment should be grounded and bonded to prevent accumulation of static charge.

**Storage Temperature:** [Ambient]

**Storage Pressure:** [Ambient]

**Suitable Containers/Packing:** Drums; Tank Cars; Tank Trucks; Barges

**Suitable Materials and Coatings (Chemical Compatibility):** Carbon Steel; Stainless Steel; Polyester; Teflon; Polyethylene; Polypropylene

**Unsuitable Materials and Coatings:** Butyl Rubber; Polystyrene; Ethylene-propylene-diene monomer (EPDM); Natural Rubber

**8. EXPOSURE CONTROLS: PERSONAL PROTECTION**

**EXPOSURE LIMIT VALUES**

**Exposure limits/standards (Note: Exposure limits are not additive)**

Occupational Exposure Limits

Substance Name	Form	Limit / Standard			Note	Source
CYCLOHEXANE		TWA	100 ppm			ACGIH
HEPTANE AND ISOMERS		TWA	1640 mg/m3	400 ppm		ACGIH
METHYLCYCLOHEXANE		TWA	400 ppm			ACGIH
n-Hexane		TWA	50 ppm		Skin	ACGIH
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	Vapour.	RCP -TWA	600 mg/m3	159 ppm	Total Hydrocarbons	ExxonMobil

**Engineering Controls**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded. Use explosionproof ventilation equipment.

**Personal Protective Equipment**

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:**

If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator Type A filter material For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin/ Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: Chemical/oil resistant clothing is recommended.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Nitrile

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### **ENVIRONMENTAL CONTROLS**

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of Measurement	Typical Value
Appearance	-	Colorless Liquid
Odour	-	Mild Petroleum
pH	-	No data available
Boiling point	°C	75-115
Melting point	°C	< 0
Flash point	°C	-15
Autoignition Temperature	°C	>200
Decomposition Temperature	°C	No data available
Lower/Upper Flammability Limits	%V	1.0-7.0
Density @ 15°C	g/cm <sup>3</sup>	0.720
Specific Gravity @ 15°C	-	0.721
Viscosity @ 25°C	cSt.s	0.56
Vapor pressure	kPa	8.65 (64.88 mm Hg) at 20 °C 31.47 (236.03 mm Hg) at 50°C 19.44(145.8 mm Hg) at 38°C
Vapor density	kPa (Air = 1)	No data available
Evaporation Rate	(n-Butyl acetate = 1)	6
Water Solubility	g/l	Negligible
Solubility in other solvents Partition coefficient	(n-octanol/water)	No data available
Coefficient of Thermal Expansion	per Deg °C	0.00126

The values listed are indicative of this product's physical and chemical properties. For a full product specification, please consult the Product Data Sheet.

### 10. STABILITY AND REACTIVITY

#### **Chemical Stability**

Material is stable under normal conditions.

#### **Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

#### **Hazardous decomposition products**

Material does not decompose at ambient temperatures.

#### **Hazardous reactions**

Hazardous polymerization will not occur.

**Materials to Avoid**

Strong oxidisers

**11. TOXICOLOGICAL INFORMATION****Acute Toxicity**

<u>Route of Exposure</u>	<u>Conclusion / Remarks</u>
<b>Inhalation</b>	
Toxicity (Rat): LC50 > 20 mg/l	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
<b>Ingestion</b>	
Toxicity (Rat): LD50 > 5000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
<b>Skin</b>	
Toxicity (Rabbit): LD50 > 3350 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Irritation: Data available.	Irritating to the skin. Based on test data for structurally similar materials.
<b>Eye</b>	
Irritation: Data available.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials.

**OTHER HEALTH EFFECTS FROM SHORT AND LONG TERM EXPOSURE**

Anticipated health effects from sub-chronic, chronic, respiratory or skin sensitization, mutagenicity, reproductive toxicity, carcinogenicity, target organ toxicity (single exposure or repeated exposure), aspiration toxicity and other effects based on human experience and/or experimental data.

**For the product itself:** Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Very high exposure (confined spaces / abuse) to light hydrocarbons may result in abnormal heart rhythm (arrhythmias). Concurrent high stress levels and/or co-exposure to high levels of hydrocarbons (above occupational exposure limits), and to heart-stimulating substances like epinephrine, nasal decongestants, asthma drugs, or cardiovascular drugs may initiate arrhythmias.

**Contains:** An ingredient or ingredients that are classified as toxic to a specific target organ from a repeated exposure.

N-HEXANE: Prolonged and/or repeated exposures to n-Hexane can cause progressive and potentially irreversible damage to the peripheral nervous system (e.g. fingers, feet, arms, legs, etc.). Simultaneous exposure to Methyl Ethyl Ketone (MEK) or Methyl Isobutyl Ketone (MIBK) and n-Hexane can potentiate the risk of adverse effects from n-Hexane on the peripheral nervous system. n-Hexane has been shown to cause testicular damage at high doses in male rats. The relevance of this effect for humans is unknown.

**IARC Classification:** The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

**12. ECOLOGICAL INFORMATION****ECOTOXICITY**

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment..

**Mobility**

Material -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

**PERSISTENCE AND DEGRADABILITY**

**Biodegradation:**

Material -- Expected to be readily biodegradable.

**Atmospheric Oxidation:**

Material -- Expected to degrade rapidly in air

**OTHER ECOLOGICAL INFORMATION**

**VOC:** Yes.

**13. DISPOSAL CONSIDERATIONS**

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

**DISPOSAL RECOMMENDATIONS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

**Empty Container Warning**

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

**14. TRANSPORT INFORMATION**

Road and Rail Transport		Marine Transport		Air Transport	
UN. Number	3295	UN. Number	3295	UN. Number	3295
Class/Item	3	Class/Item	3	Class/Item	3
Hazard Symbol	Flammable Liquid	Hazard Symbol	Flammable Liquid	Hazard Symbol	Flammable Liquid
Proper Shipping Name	HYDROCARBONS, LIQUID, N.O.S.	Proper Shipping Name	HYDROCARBONS, LIQUID, N.O.S.	Proper Shipping Name	HYDROCARBONS, LIQUID, N.O.S.
Packing Group	II	Packing Group	II	Packing Group	II
		Marine Pollutant	No		

**Dangerous Goods Segregation**

This product is classed as Dangerous Goods Class 3, packing group II. Please consult the Australian Dangerous Goods Code for Transport by Road and Rail for information.

**15. REGULATORY INFORMATION**

This material is considered hazardous according to the classification criteria of the Hazard Classification and Communication System for Hazardous Materials BE 2555.

**REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**


**Hazardous Substance Act BE2535:** Regulated

**Listed or exempt from listing/notification on the following chemical inventories:** AICS, DSL, ENCS, IECS, KECI, PICCS, TCSI, TSCA



## 16. OTHER INFORMATION

National Fire Protection Association (USA) :



SDS Distribution :

The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty of guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.

Prepared By :

Quality Control Department / Global Chemie ASCC Limited

**Abbreviations:**

AICS: Australian Inventory of Chemical Substances

CAS Number: Chemical Abstracts Number

IARC: International Agency for Research on Cancer

N/A: not available

NOHSC: National Occupational Health and Safety

Council GHS: Global Harmonized System

**References:**

- Supplier Material Safety Data Sheets
- <http://chem.sis.nlm.nih.gov/chemidplus> (October 18)
- <http://hsis.ascc.gov.au/SearchHS.aspx> (October 18)
- Ecotoxicology data: [http://cfpub.epa.gov/ecotox/quick\\_query.htm](http://cfpub.epa.gov/ecotox/quick_query.htm) (October 18)
- *Sax's Dangerous Properties of Industrial Materials*, Richard J. Lewis Snr., pub. Canada (2000)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. No warranty and guarantee are expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product. For further information, please contact Global Chemie ASCC Limited.